

RANGER HALF WINDSHIELD

KIT PN: 2876960

Application Polaris Ranger Model Year 2009 +



Before you begin, read these instructions and check to be sure all parts and tools are accounted for. Please retain these installation instructions for future reference and parts ordering information.

Kit Components:

<u>QTY.</u>	<u>Part Description</u>	<u>QTY.</u>	<u>Part Description</u>
1	Windshield Assembly	4	¼-20 Nylock Flange Nuts
4	Rubber Coated Clamps	4	¼-20 x 1.00" Screws
1	Instruction Sheet	4	¼ Fender Washers

IMPORTANT: Your Polaris accessory kit is exclusively designed for your Polaris vehicle. Please read the installation instructions and operator's manual thoroughly before beginning. Installation of any item is easier if the vehicle is clean and free of debris. **Approximate Installation Time:** 15 Minutes

REPLACEMENT PARTS:

Hardware kit: 2876960H

Trim: 2857782

INSTALLATION INSTRUCTIONS

1. **Install windshield on machine:** Refer to **Figure #1**. Position windshield onto machine. Place the four clamps on the cab frame. Now install the windshield to the clamps using the remaining 4 screws, fender washers, and flange nuts as shown. **NOTE:** Torque fasteners to 25 in-lbs. – do not over tighten.

Cleaning Instructions:

1. Use a high pressure water supply to rinse the large dirt particles from the windshield.
2. Once the majority of dirt is removed, use warm soapy water and a cotton terry cloth to wash all windshield components.
3. Rinse thoroughly and allow to air dry.
4. Use a premium plastic cleaner/polish such as **Plexus®** or **Novus®** to properly clean the viewing area of the windshield. (Never use paper towels, only use clean cotton terry cloths.)

